



Type	Other Machines
Brand	PROCOMAC
Model	OZOSTERIL 3000
Number	P1041
Condition	IN GOOD CONDITIONS

## Characteristics

### PROCOMAC Oozonator

This product ozone generator applies a technique of cooling air instead of water, able to simplify the connection, installation, dismantling and operation and also help contain costs.

Especially suitable for applications in air handling systems for pilot and laboratory and compact plants for water treatment plants.

### Technical characteristics:

It is built on sturdy steel frame and tubular profiles with removable panels on each side, closed with hexagonal screws.

Effluvia system: pyrex ampoule diameter 36 x 650 mm diameter

Refrigeration air through the helical fan for both inside blisters and

Primary voltage: 380 V -50 Hz

Production capacity: continuously adjustable from 0.6 to 12 gb with air supply 1.2 to 24 g / h with oxygen

Phone:  
+34 968 693 140

Email:  
info@inter-maquinasagUILAR.com

Web:  
inter-maquinasagUILAR.com

Main components of the installation:Ozone generator

- make: Ozone Elettronica Internazionale
- Type: Triozon 10
- Power supply: 380 V 50 Hz

Contact tank:

- Make: Ghizzoni
- diameter: 406 mm
- Cylindrical Height: 1200 mm
- Capacity: 150 liters
- Material: AISI 316

Booster pump:

- Make: C.S.F.
- Type: CV03 Q.4,5 220 / 380V, 500HZ
- Material: AISI 316

Ejector

- Make: Procomac
- Type: 90059101

Redox

- Maker: B & C
- Type: MV545

Security valve:

-Make Tassalini

-Type: 631D25 / 000

-Material: 304-T

Electrovalve:

-Manufacturer: GEMU

-type 105 in teflon

**URL**

<https://www.inter-maquinasagUILAR.com/en/productos/varios/procomac-ozosteril-3000>